

LAW OFFICES
McGuireWoods LLP
1750 TYSONS BOULEVARD, SUITE 1800
MCLEAN, VIRGINIA 22102

APPLICATION
FOR
UNITED STATES
LETTERS PATENT

Applicants: Thomas Brendel
For: WHEELCHAIR WITH CASTORS
Docket No.: 03100131US

Wheelchair with castors

The invention relates to a wheelchair having two driven wheels and at least one castor which is mounted in a rotatable manner in a fork which can be pivoted about a vertical axis, the fork being connected to a steering linkage.

Such a wheelchair is known, for example, from EP 0 324 101 A2. In the case of such wheelchairs, the two drive wheels are driven by an electric motor.

Electric wheelchairs are generally designed for use outdoors and thus for covering relatively large distances on roads and paths. In order to increase the tracking stability, the steering system is configured as a positive steering system. Rather than one or two central castors being provided, it is usually the case that in each case one castor is mounted in a fork in each case on both sides of the wheelchair. The positive steering usually takes place in that an electric servomotor keeps the forks of the castors on track over the steering angle set by the user. Use of the steering linkage, via which the forks are coupled to one another, limits the possible steering angle, with the result that the smallest turning circle is a few meters. Such wheelchairs are thus only suitable to a limited extent, if at all, indoors or in confined spaces.

Wheelchairs which are to be used in confined spaces usually have freely steered castors. These freely steered castors are mounted in forks which can be rotated freely about their vertical axis. Each drive wheel is driven by a dedicated electric motor. The direction of travel predetermined by the user is maintained not via the castors, but by way of different activation of the drive wheels. Depending on the direction of travel, the castors bring themselves on

track by way of a correspondingly predetermined
castor action. On account of the forks being able to
rotate freely independently of one another, it is
possible to realize a small turning circle (the
5 wheelchair can be rotated more or less on the spot).
However, this advantage comes at the expense of
considerably poorer tracking stability, with the result
that such wheelchairs are not suitable for use over
long distances outdoors.

10

Taking this problem as the departure point, the
intention is to improve an electrically driven
wheelchair to the extent that it has both a high level
of tracking stability and a small turning circle, with
15 the result that it is suitable both for long distances
outdoors and for use in confined spaces.

In order to solve the problem, a wheelchair of the
generic type is distinguished in that the connection
20 between the fork and the steering linkage is
releasable.

This configuration makes it possible to change over
between positive steering and free steering. For the
25 long distances and a high level of tracking stability,
the at least one fork is, or two forks spaced apart by
a track width are, connected to the steering linkage,
with the result that it is only possible for the forks
to be pivoted about the vertical axis. In order to
30 reduce the turning circle, the forks are separated from
the steering linkage. The direction of travel of the
wheelchair is then predetermined by way of individual
activation of the drive wheels and the castors can
rotate freely through 360°, with the result that the
35 wheelchair can be rotated more or less on the spot.

The forks are preferably mounted in a rotatable manner
in a bushing which is fixed to the frame of the
wheelchair.

The operations of blocking the forks in relation to the steering linkage and separating them therefrom preferably take place mechanically, the blockage taking place in the straight-ahead position.

5

The forks are mounted in the bushing via a fork pin. The blockage of the forks preferably takes place by means of a bolt which can be pushed, transversely to the vertical axis, into a recess provided in the fork pin. The recess may be designed as a through-passage bore.

15 It is advantageous, in particular, if the bolt is subjected to loading by a compression spring, with the result that secure latching of the bolt in the recess in the fork pin is possible. The recess in the fork pin is circumferentially configured such that the bolt latches of its own accord therein when it coincides with the recess.

20

The bolt can be displaced via a pivot lever, which is manually actuated by the user or moved in an electromotive manner by the control means.

25 It is advantageous if the pivot lever is mounted on a spindle fastened in the bushing.

30 The exemplary embodiments of the invention are explained in more detail hereinbelow with the aid of a drawing, in which:

figure 1 shows the schematic side view of a wheelchair;

35 figure 2 shows a partial illustration corresponding to the viewing arrow II according to figure 1;

figure 3 shows the detail corresponding to viewing arrow III according to figure 2;

- figure 4 shows an enlarged partial illustration from figure 2, in the positively steered mode;
- 5 figure 5 shows the view according to figure 4 in the freely steered mode;
- figure 6 shows a perspective partial illustration of the steering system in the unlocked state of the forks;
- 10 figure 7 shows a perspective partial illustration of the steering system in the locked position of the forks;
- 15 figure 8 shows a partial illustration, corresponding to figure 5, of a further exemplary embodiment;
- 20 figure 9 shows a partial illustration, corresponding to figure 4, of the exemplary embodiment according to figure 8;
- figure 10 shows a partial illustration corresponding to the viewing arrow II according to figure 1 in the case of the further exemplary embodiment;
- 25 figure 11 shows a partial illustration, in perspective, of the further exemplary embodiment;
- 30 figure 12 shows the partial illustration, in perspective, of the steering system of the further exemplary embodiment in the locked state;
- 35 figure 13 shows a perspective illustration of the locking mechanism according to the exemplary embodiment in the locked position; and

figure 14 shows the illustration according to figure 13
in the unlocked position.

5 The electric wheelchair essentially comprises the
frame 20, which inter alia also accommodates the seat
system 60, and further comprises the drive wheels 40,
which can be driven independently via in each case one
drive motor - not illustrated specifically here - and
the non-driven castors 1, 1a. The castors 1, 1a are
10 mounted in a rotatable manner in forks 2, 2a. The
steering system of the wheelchair is of symmetrical
construction, so that the invention will be explained
further in relation to one side (on the right in
figure 2).

15 The fork 2 has an upwardly projecting fork pin 4 which
is mounted in a freely rotatable manner, via
rolling-contact bearings 6, in a bushing 5 connected to
the frame 20.

20 The forks 2, 2a are connected to one another via the
steering linkage 3, 3', 30, 3'', 3a. The outer ends
3, 3a of the steering linkage are provided with a
horizontally running through-passage bore 3₁ and a
25 vertical bore (not designated specifically) which
accommodates the fork pin 4. The fork pin 4 has a
recess 13 running coaxially in relation to the
through-passage bore 3₁.

30 A bolt 12 is latched in the recess 13 in the positively
steered state, said bolt preventing the fork 2 from
being able to rotate in the bushing 5. The bolt 12 is
subjected to loading by a compression spring 14 and is
connected to an actuating lever 10, which is mounted in
35 a pivotable manner on a spindle 11 and, in turn,
interacts with a pivot lever 8, which can be pivoted in
a vertical plane on a spindle 9 fastened in the
bushing 5. The pivoting movement of the pivot lever 8
is initiated by the connecting linkage 7 being pivoted

correspondingly. For this purpose, the front end of the pivot lever 8 has a rounded protuberance (see figures 6 and 7).

5 In the positively steered mode (blocked fork pin 4), the direction of travel predetermined by the user is set via the steering servo 50 by the latter rotating the pivotably mounted plate 30, which bears the links 3', 3'' at its outer ends. The pivoting angle of the
10 forks 2, 2a, and thus the steering angle of the wheels 1, 1a, is determined by the defined pivoting-angle range of the plate 30. In this mode, the mechanical coupling of the forks 2, 2a achieves a high level of tracking stability for the wheelchair, which makes it
15 possible for the wheelchair to be controlled to good effect over long distances outdoors.

In order to make a small turning circle of the wheelchair possible when the latter is used, for
20 example, in confined spaces, the forks 2, 2a can be unlocked by the bolt 12 being drawn out of the recess 13 in the fork pin 4 counter to the force of the compression spring 14, by means of the lever 10. The fork pin 4 can then be rotated through 360° in relation
25 to the ends 3, 3a of the steering linkage. The connection between the forks 2, 2a is thus eliminated. Rather than being predetermined via the servomotor 50, the direction of travel of the wheelchair can now only be predetermined by the drive wheels 40 being driven
30 differently by way of the drive motors assigned to them. Corresponding to the castor action of the forks 2, 2a, the wheel position of the castors 1, 1a is then established in accordance with the direction of travel predetermined by the user. If the drive wheels are
35 driven in opposite directions, the castors 1, 1a position themselves transversely to the straight-ahead position, with the result that it is possible for the wheelchair to rotate on the spot.

The activation of the motors of the drive wheels and of the servomotor 50 (steering servo) is achieved by means of suitable software which changes over the steering movement predetermined by the user in accordance with the desired direction of travel. The locking device may be actuated in an electromotive manner or by hand.

The recess 13 in the fork pin 4 is countersunk around the circumference and thus configured such that the bolt 12, which is subjected to loading by a compression spring, automatically and easily engages in the recess 13 when it coincides coaxially with the through-passage bore 3₁ provided in the end 3 of the steering linkage.

15

Figures 8-14 show a further exemplary embodiment of the locking device. Equivalent components in the two exemplary embodiments are provided with the same designations. In the case of this exemplary embodiment, the bolt 12 is moved by a linear movement being initiated. The fork pin 4 is provided with a countersunk bore 13. The bore 12 is accommodated in the steering linkage and subjected to the action of the compression spring 14, which forces it in the direction of the recess 13. The vertically displaceable lever 15 is provided with a run-on slope 16, which interacts with a radial shoulder 12a on the bolt 12. The movement of the lever 15 is initiated via the pivot lever 8, which is mounted in a pivotable manner on the spindle 9. If the lever 8 is changed over, by motor or manual actuation, from its position which is shown in figures 8 and 14 into the position shown in figures 9 and 13, the bolt 12, via its shoulder 12a, forces the lever 15 upward along the run-on slope 16 and is pushed into the recess 13 by the compression spring 14. In order to make this horizontal movement of the bolt 12 possible, the lever 15 is provided with a correspondingly wide bore 17. As long as the bolt 12 engages in the recess 13, the positively steered mode

is set. In order to change into the freely steered mode, the lever 8 is pivoted over in the other direction, with the result that it forces the lever 15 downward, as a result of which, via the run-on slope 5 16, the bolt is forced out of the recess 13 and the compression spring 14, at the same time, is subjected to stressing.

10 The two pivot levers 8 are connected to one another via the connecting linkage 7. The pivoting movement is initiated via the actuator 70, of which the piston rod interacts with a fork 18 fastened on the connecting linkage 7.

List of designations

1	Castor
1a	Castor
2	Fork
2a	Fork
3	Outer end of the steering linkage
3a	Outer end of the steering linkage
3'	Steering linkage
3''	Steering linkage
3 ₁	Through-passage bore
4	Fork pin
5	Bushing
5a	Bushing
6	Rolling-contact bearing
7	Connecting linkage
8	Pivot lever
8a	Pivot lever
9	Spindle
10	Lever
11	Pivot spindle
12	Bolt
12a	Radial shoulder
13	Recess
14	Compression spring
15	Lever
16	Run-on slope
17	Bore
18	Fork
20	Framework
30	Plate
40	Drive wheel
50	Servomotor/steering servo
60	Seat system
70	Actuator
H	Vertical axis